

We offer the Sensor safety pocket / Thermowell / Sleeve

from

Tantalum, Niobium, Titanium

Ti-Pd, Zirconium, Nickel, Nicrofer, Hastelloy

Inconel, Monel, Duplex steel and Ceramic

Quality

- ▶ ASME IX coded welding
- ▶ Gun drill facility to ASTM A182 or BS 503
- ▶ NACE Heat treatment MR-01-75.
- ▶ Hydrostatic pressure test up to 300 kg / cm².
- ▶ Pneumatic test up to 30 kg / cm² for 2 hours.
- ▶ Dye penetrant and Radiography test as and when required.

Availability

- ▶ Bar Stock Thermowells
 - Screwed construction - Flat tip well for low pressure.
 - Flange construction - Domed tip well for high pressure.
- ▶ Fabricated Sleeves
 - Seam weld Sleeve
 - Seamless Sleeve
 - ◆ Seamless exotic metal sleeves.
 - ◆ Seamless ceramic tube wells.
 - ◆ Polymer tube wells.
- ▶ To prevent Crevice corrosion
- Oxide layer coating on Sleeves
- ▶ Thermowell with the accessories of plug or cap nut and chain.



Ti Anode Fabricators Pvt. Ltd.
An ISO 9001 : 2008 Company

48, Noothanchary, Madambakkam, Chennai - 126, INDIA.
Ph.: +91 44 2278 1148, +9194445 69900 | Fax: 2278 1362
Email: marketing@tiaano.com | Web: www.tianode.com